

1. (Amended) A device for focusing a charged solute comprising:

12 a first chamber for receiving a fluid medium, the first chamber having an inlet for introducing a first liquid to the chamber and an outlet for exiting the first liquid from the chamber;

a second chamber comprising an electrode array, the second chamber having an inlet for introducing a second liquid to the chamber and an outlet for exiting the second liquid from the chamber;

a porous material separating the first and second chambers; and

means for dynamically controlling the voltage applied to the electrode array.

47. (Amended) A method for focusing a charged solute in a fluid medium comprising:

13 introducing a charged solute into a fluid medium, wherein the fluid medium is contained in a device comprising:

a first chamber for receiving the fluid medium, the first chamber having an inlet for introducing a first liquid to the chamber and an outlet for exiting the first liquid from the chamber;

a second chamber comprising an electrode array, the second chamber having an inlet for introducing a second liquid to the chamber and an outlet for exiting the second liquid from the chamber;

a porous material separating the first and second chambers; and

means for dynamically controlling the voltage applied to the electrode array; and

applying an electric field gradient to the charged solute in the fluid medium to cause the charged solute to focus in a region of the medium.

LAW OFFICES OF
CHRISTENSEN, O'CONNOR, JOHNSON, KINDNESS
1420 Fifth Avenue
Suite 2800
Seattle, Washington 98101
206 682 8100

57. (Amended) A method for focusing a charged solute comprising:
applying a charged solute to a fluid medium;
applying a hydrodynamic force to the solute in the fluid medium; and
opposing the hydrodynamic force with an electric field gradient to provide a solute focused in the fluid medium, wherein the electric field gradient is generated by an electrode array, and wherein the electric field gradient is dynamically controlled.

64. (Amended) A method for separating charged solutes comprising:
applying a mixture of charged solutes to a fluid medium;
applying a hydrodynamic force to the solutes in the fluid medium; and
opposing the hydrodynamic force with an electric field gradient to separate the charged solutes in order of their electrophoretic mobilities, wherein the electric field gradient is generated by an electrode array, and wherein the electric field gradient is dynamically controlled.

70. (New) A device for focusing a charged solute comprising:
a first chamber for receiving a fluid medium, the first chamber having an inlet for introducing a first liquid to the chamber and an outlet for exiting the first liquid from the chamber;
a second chamber comprising an electrode array, the second chamber having an inlet for introducing a second liquid to the chamber and an outlet for exiting the second liquid from the chamber, wherein the electrode array is two-dimensional; and
a porous material separating the first and second chambers.

71. (New) A method for focusing a charged solute in a fluid medium comprising:
introducing a charged solute into a fluid medium, wherein the fluid medium is contained in a device comprising:

a first chamber for receiving the fluid medium, the first chamber having an inlet for introducing a first liquid to the chamber and an outlet for exiting the first liquid from the chamber;

a second chamber comprising an electrode array, the second chamber having an inlet for introducing a second liquid to the chamber and an outlet for exiting the second liquid from the chamber, wherein the electrode array is two-dimensional; and

a porous material separating the first and second chambers;

applying an electric field gradient to the charged solute in the fluid medium to cause the charged solute to focus in a region of the medium.

72. (New) A system for focusing a solute, comprising:

a device, comprising:

a first chamber for receiving the fluid medium, the first chamber having an inlet for introducing a first liquid to the chamber and an outlet for exiting the first liquid from the chamber;

a second chamber comprising an electrode array, the second chamber having an inlet for introducing a second liquid to the chamber and an outlet for exiting the second liquid from the chamber; and

a porous material separating the first and second chambers;

a controller, comprising a plurality of controller units, wherein the plurality of controller units is in electrical communication with the electrode array;

at least one analytical instrument; and

an interface intermediate the device and the analytical instrument.

LAW OFFICES OF
CHRISTENSEN O'CONNOR JOHNSON KINDNESS
1420 Fifth Avenue
Suite 2800
Seattle, Washington 98101
206 682 8100

73. (New) The system of Claim 72, wherein the device further comprises:

at least a third chamber comprising at least a second electrode array, the at least a third chamber having an inlet for introducing at least a second liquid to the chamber and an outlet for exiting the at least a second liquid from the chamber, wherein the at least a second electrode array comprises a plurality of electrodes; and

at least a second porous material separating the first and at least a third chambers, wherein the first porous material and the at least a second porous material are on opposite sides of the first chamber, and the electrodes in the at least a second electrode array form pairs with the electrodes in the first electrode array.

74. (New) The device of Claim 72, wherein the controller dynamically monitors and sets the voltage at each electrode in response to signals from an operator.

75. (New) The device of Claim 72, wherein the controller dynamically monitors and sets the voltage at each electrode in response to signals from the at least one analytical instrument.

76. (New) The device of Claim 72, wherein the at least one analytical instrument comprises at least one of an optical detection device and a potentiometric detection device.

77. (New) The device of Claim 72, wherein the at least one analytical instrument comprises a video camera.